BUS Cables

E-BUS / KNX fixed installed





Type Cable structure

Inner conductor:
Core insulation:
Core colours:
Stranding element:
Separator:
Shielding 1:
Total shielding:
Drain wire:
Outer sheath material:
Cable external diameter:
Outer sheath colour:

Electrical data

Characteristic impedance: Conductor resistance, max.: Insulation resistance, min.: Loop resistance: Mutual capacitance: Test voltage:

Technical data

Weight: bending radius, repeated: Operating temperature range min.: Operating temperature range max.: Caloric load, approx. value: Copper weight:

Norms

Applicable standards:



2-pairs 2x2x0.8 mm

Copper, bare PVC wh, ye, rd, bk Star quad

Polyester foil over stranded bundle

Al-Foil yes PVC

app. 6,6 mm ± 0,3 mm Blue Lilac similar to RAL 4005

100 Ohm 73,2 Ohm/km 0,1 GOhm x km 146 Ohm/km max. 100 nF/km nom. 4 kV

app. 64 kg/km 95 mm -30°C +70°C 0,90 MJ/m 25,00 kg/km

EIB/KNX standard

Flame-retardant acc. to EN 50265-2-1

2-pairs 2x2x0.8 mm

Copper, bare PVC wh, ye, rd, bk Star quad

Polyester foil over stranded bundle

Al-Foil yes PVC

app. 6,6 mm \pm 0,3 mm Green similar to RAL 6010

100 Ohm 73,2 Ohm/km 0,1 GOhm x km 146 Ohm/km max. 100 nF/km nom. 4 kV

app. 64 kg/km 95 mm

-30°C +70°C 0,90 MJ/m 25,00 kg/km

EIB/KNX standard

Flame-retardant acc. to EN 50265-2-1

Application

HELUKABEL® E-BUS EIB/KNX PVC for fixed installation. The E-Bus cable is intended for transmission of bus signals in intelligent building systems. The cables ensure perfect communication in compliance with EIB regulations. They can be installed over, in and under plaster, in conduits and cable channels, in dry, damp and wet rooms as well as outdoors - if protected from direct sunlight. Wiring together with high-power cables is possible without limitation. The EIB/KNX bus can be used to control lighting, blinds, heating, ventilation, indicator boards etc.

Part no. 81081, E-BUS / KNX 81663, E-BUS / KNX

Dimensions and specifications may be changed without prior notice.